

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problems Mailbox.**

30GF-9118
PATENTIN THE CLAIMS

1. (canceled)

2. (currently amended) A control circuit for configuring at least one I/O module connector pin, said circuit comprising at least one port controlling a configuration of the at least one pin, said at least one port comprises at least one of a Pull-Down (PD) port, a Pull-Up (PU) port, a Discrete High (DH) port, a Discrete Low (DL) port, a positive 15 volt (P15V) port, a negative 15 volt (N15V) port, a range (RANGE) port, and a voltage out (VOUT) port, said circuit utilizing a single digital to analog converter (DAC) for each said pin to implement a discrete digital mode and an analog mode.

3. (currently amended) A control circuit for configuring at least one I/O module connector pin, said circuit comprising:

at least one port controlling a configuration of the at least one pin; and

at least one switch assembly comprising a solid state switch, said at least one port controlling whether a respective said at least one solid state switch is in an open state or a closed state; and

a single digital to analog converter (DAC) used for each said pin to implement a discrete digital mode and an analog mode.

4. (original) A control circuit in accordance with Claim 3 wherein the at least one switch assembly comprises at least one of a Pull-Down switch, a Pull-Up switch, a Discrete High switch, a Discrete Low switch, a positive 15 volt switch, a negative 15 volt switch, a range switch, and a voltage out switch.

5. (original) A control circuit in accordance with Claim 3 wherein the configuration of the at least one switch assembly determines the configuration of the at least one pin.

6. (canceled)

7. (currently amended) An I/O module comprising:

30GF-9118
PATENT

sub C2
at least one connector pin; and

a control circuit comprising a plurality of solid state switches, said solid state switches controlling a configuration of the at least one pin; and

a single digital to analog converter (DAC) for each said pin to implement a discrete digital mode and an analog mode.

8. (original) An I/O module in accordance with Claim 7 wherein said circuit further comprising at least one port controlling a configuration of a respective at least one switch.

9. (previously presented) An I/O module in accordance with Claim 8 wherein an energization state of each said at least one port controlling a state of a respective at least one switch.

10. (original) An I/O module in accordance with Claim 8 wherein said at least one port comprises at least one of a Pull-Down (PD) port, a Pull-Up (PU) port, a Discrete High (DH) port, a Discrete Low (DL) port, a positive 15 volt (P15V) port, a negative 15 volt (N15V) port, a range (RANGE) port, and a voltage out (VOUT) port.

11. (original) An I/O module in accordance with Claim 7 wherein said switches comprising at least one of a Pull-Down switch, a Pull-Up switch, a Discrete High switch, a Discrete Low switch, a positive 15 volt switch, a negative 15 volt switch, a range switch, and a voltage out switch.

12. (canceled)

sub C2
13. (currently amended) A PLC comprising:

a CPU; and

an I/O module comprising at least one connector pin and a control circuit comprising a plurality of ports, a configuration of the at least one connector pin determined by an energization state of said ports; and

30GF-9118
PATENT

subC2
13. a single digital to analog converter (DAC) for each said connector pin to implement a discrete digital mode and an analog mode.

28
14. (original) A PLC in accordance with Claim 13 wherein said at least one port comprises at least one of a Pull-Down (PD) port, a Pull-Up (PU) port, a Discrete High (DH) port, a Discrete Low (DL) port, a positive 15 volt (P15V) port, a negative 15 volt (N15V) port, a range (RANGE) port, and a voltage out (VOUT) port.

15. (original) A PLC in accordance with Claim 13 further comprising at least one switch assembly comprising a switch, said at least one port controlling whether a respective said at least one switch is in an open state or a closed state.

16. (original) A PLC in accordance with Claim 15 wherein the at least one switch assembly comprises at least one of a Pull-Down switch, a Pull-Up switch, a Discrete High switch, a Discrete Low switch, a positive 15 volt switch, a negative 15 volt switch, a range switch, and a voltage out switch.

17. (currently amended) A PLC in accordance with Claim 15 wherein the configuration of the at least one switch assembly determines the configuration of said at least one connector pin.

✓ 18. (canceled)

subC2
19. (currently amended) A method for configuring at least one connector pin utilizing a control circuit, the control circuit including at least one port, said method comprising:
providing an energization state to the at least one port; and
controlling a configuration of the at least one connector pin utilizing the energization state of the at least one port; and
utilizing a single digital to analog converter (DAC) for each said connector pin to implement a discrete digital mode and an analog mode.

30GF-9118
PATENT

subC2 > 20. (original) A method in accordance with Claim 19 wherein the at least one port comprises at least one of a Pull-Down (PD) port, a Pull-Up (PU) port, a Discrete High (DH) port, a Discrete Low (DL) port, a positive 15 volt (P15V) port, a negative 15 volt (N15V) port, a range (RANGE) port, and a voltage out (VOUT) port.

PA 21. (original) A method in accordance with Claim 19 wherein the control circuit includes at least one switch assembly including a switch, said method further comprising:

utilizing the energization state of the at least one port to control whether a respective at least one switch is in an open state or a closed state; and

controlling a configuration of the at least one connector pin utilizing the state of the at least one switch.

22. (original) A method in accordance with Claim 21 wherein the at least one switch assembly includes at least one of a Pull-Down switch, a Pull-Up switch, a Discrete High switch, a Discrete Low switch, a positive 15 volt switch, a negative 15 volt switch, a range switch, and a voltage out switch.

✓ 23. (canceled)

subC2 > 24. (currently amended) An I/O module comprising:

at least one connector pin; and

a control circuit comprising:

a plurality of switches controlling a configuration of said at least one pin and at least one port controlling a configuration of a respective at least one switch, an energization state of each said at least one port controlling a state of a respective at least one switch; and

a single digital to analog converter (DAC) for each said pin to implement a discrete digital mode and an analog mode.

25. (previously presented) An I/O module comprising:

30GF-9118
PATENT

pubca >
at least one connector pin; and

a control circuit comprising a plurality of switches controlling a configuration of said at least one pin, said circuit utilizing a single DAC for each said connector pin to implement a discrete digital mode and an analog mode.

26. (previously presented) An I/O module in accordance with Claim 25 wherein said circuit further comprising at least one port controlling a configuration of a respective at least one switch.

27. (canceled)

pubca >
28. (currently amended) A method for configuring at least one connector pin utilizing a control circuit, said method comprising controlling a configuration of the at least one connector pin utilizing a single DAC for each pin of the at least one ~~connector pin~~ ~~connector pins~~ to implement a ~~discrete~~ ~~discrete~~ digital mode and an analog mode.

29. (previously presented) A method in accordance with Claim 28 wherein the control circuit includes at least one port, said method further comprising providing an energization state to the at least one port to control a configuration of the at least one connector pin.

30. (previously presented) A method in accordance with Claim 29 wherein the control circuit includes at least one switch assembly including a switch, said method further comprising:

utilizing the energization state of the at least one port to control whether a respective at least one switch is in an open state or a closed state; and

controlling a configuration of the at least one connector pin utilizing the state of the at least one switch.

31. (previously presented) A method in accordance with Claim 30 wherein the at least one switch assembly includes at least one of a Pull-Down switch, a Pull-Up switch, a

30GF-9118
PATENT

Handwritten signature/initials
Discrete High switch, a Discrete Low switch, a positive 15 volt switch, a negative 15 volt switch,
a range switch, and a voltage out switch.